

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max.Air Pressure (KPa)	Max.Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	30"	245/30R22	XL	BSW	8.5	-	92W	630	1389	340	50	8.7	248	707
2		255/30R24	XL	BSW	9.0	-	97W	730	1609	340	50	8.7	260	764
3		295/30R26	XL	BSW	10.5	-	107W	975	2149	340	50	8.7	301	838
4		305/30R26	XL	BSW	11.0	-	109V	1030	2271	340	50	8.7	313	844
5	35"	265/35R22	XL	BSW	9.5	-	102V	850	1874	340	50	8.7	271	745
6		295/35R24	XL	BSW	10.5	-	110V	1060	2337	340	50	8.7	301	816
7		305/35R24	XL	BSW	11.0	-	112V	1120	2469	340	50	8.7	313	824
8	40"	245/40R20	XL	BSW	8.5	-	99W	775	1709	340	50	8.7	248	704
9		265/40R22	XL	BSW	9.5	-	106V	950	2094	340	50	8.7	271	771
10		275/40R20	XL	BSW	9.5	-	106V	950	2094	340	50	8.7	278	728
11		275/40R20	XL	BSW	9.5	-	106W	950	2094	340	50	8.7	278	728
12		305/40R22	XL	BSW	11.0	-	114V	1180	2601	340	50	8.7	313	803
13	45"	275/45R20	XL	BSW	9.0	-	110V	1060	2337	340	50	8.7	273	756
14		275/45R20	XL	BSW	9.0	-	110W	1060	2337	340	50	8.7	273	756
15		285/45R22	XL	BSW	9.5	-	114V	1180	2601	340	50	8.7	285	815
16		305/45R22	XL	BSW	10.0	-	118V	1320	2910	340	50	8.7	303	833
17	50"	265/50R20	XL	BSW	8.5	-	111V	1090	2403	340	50	8.7	277	774
18		285/50R20	XL	BSW	9.0	-	116V	1250	2756	340	50	8.7	297	794
19	55"	275/55R20	XL	BSW	8.5	-	117V	1285	2833	340	50	8.7	284	810
20	60"	225/60R17	XL	BSW	6.5	-	103V	875	1929	340	50	8.7	228	702
21		275/60R20	SL	BSW	8.0	-	115V	1215	2679	350	51	8.7	279	838
22	65"	225/65R17	XL	BSW	6.5	-	106V	950	2094	340	50	8.7	228	724