

NO.	Series	Size	SL/XL	Sidewall Type	Rim	PR	LI/SS	Max. Load Capacity (KG)	Max. Load Capacity (LBS)	Max.Air Pressure (KPa)	Max.Air Pressure (PSI)	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)
1	55"	205/55R16	SL	BSW	6.5	-	91T	615	1356	350	51	10	214	632
2	60"	185/60R14	SL	BSW	5.5	-	82T	475	1047	350	51	10	189	578
3		195/60R14	SL	BSW	6.0	-	86T	530	1168	350	51	10	201	590
4		225/60R16	SL	BSW	6.5	-	98T	750	1653	350	51	10	228	676
5	65"	175/65R14	SL	BSW	5.0	-	82T	475	1047	350	51	10	177	584
6		185/65R14	SL	BSW	5.5	-	86T	530	1168	350	51	10	189	596
7		185/65R15	SL	BSW	5.5	-	88T	560	1235	350	51	10	189	621
8		195/65R15	SL	BSW	6.0	-	91T	615	1356	350	51	10	201	635
9	70"	235/65R17	XL	BSW	7.0	-	108T	1000	2205	340	50	10	240	738
10		165/70R13	SL	BSW	5.0	-	79T	437	963	350	51	10	170	562
11		175/70R13	SL	BSW	5.0	-	82T	475	1047	350	51	10	177	576
12		205/70R14	XL	BSW	6.0	-	98T	750	1653	340	50	10	209	644
13		205/70R15C	-	BSW	6.0	8	106/104R	950/900	2094/1984	450	65	10	209	669
14		235/70R16	SL	BSW	7.0	-	106T	950	2094	350	51	10	240	736
15	75"	185/75R16C	-	BSW	5.0	8	104/102R	900/850	1984/1874	475	69	10	184	684
16		235/75R15	SL	BSW	6.5	-	105T	925	2039	350	51	10	235	733